



MINI SPOT

Proiettore orientabile a LED
Adjustable LED projector

Codice | Code

103 ✕ 4 ▲ ■ ●

Potenza | Power

9,5 W

Alimentazione | Power supply

230 V

48 V

Finitura colore | Color finishing

○ white

● black

● aluminium

Riferimento CCT | CCT reference

3000K

4000K

Ottica | Optic

25°

46°

Controllo | Control

DALI

Bluetooth

Materiale | Material

Alluminio verniciato

Painted aluminum

Temperatura di utilizzo | Operating temperature

-20°C to +40°C

Durata media stimata | Average estimated duration

L80/B10 50000 h (Tc 50° C)

Sicurezza | Safety

IP20 Classe III



✕

7

8

▲

1

2

9

■

1

2



●

2


4

Proiettore orientabile a LED. Corpo in alluminio tornito verniciato in bianco, nero e grigio. Orientabile da 0° a 90° sul piano verticale e di 358° su quello orizzontale. Montaggio a binario elettrificato a 48V con alimentatore elettronico a scomparsa all'interno dell'adattatore. Possibilità di fissaggio con base a plafone. LED a tecnologia COB ad alta efficienza disponibile in temperature di colore 3000K/4000K, con CRI da maggiore 84 a 97. Ottica di precisione in policarbonato, con schermo di protezione. Durata nominale 50 000h, L80/B10. Classe d'isolamento III, grado di protezione IP20.


Adjustable LED projector. Die-cast aluminum body painted in white, black and grey. Adjustable from 0 to 90, on the vertical plane and 358 on the horizontal. Electrified rail mounting at 220-240vac 50-60hz with electronic driver in the adapter. Dimmable version with Dali system, Bluetooth available upon request. Fixing possibility with ceiling base. High efficiency COB technology LED available in 3000K/4000K color temperatures, with CRI from higher 84 to 97. Precision polycarbonate optics, with transparent protective glass. Rated life 50 000h, L80/B10. Insulation class II, protection type IP20.


Disegno Tecnico
 Technical Drawing

Emissione del flusso luminoso
 Luminous flux emission


Codice base Base code	Potenza Power	Colore Color	CCT CCT	Ottica Optics	Lumen (lm)		Alimentazione Power supply	Peso Weight
					3000K	4000K		
1038.4 ▲ ■ ●	9,5 W	1 white 2 black 9 grey	1 3000K 2 4000K	2 25° 4 46°	950	965	48 V	300 g
1037.4 ▲ ■ ●	9,5 W	1 white 2 black 9 grey	1 3000K 2 4000K	2 25° 4 46°	950	965	230 V	300 g

Curva fotometrica
 Photometric chart


25°



46°